



Electro-hydraulic twin-ram lift, 3.5 t with adjustable swivel arms



Item no.	Piece/set	Part of the approval according to order no. 16062:
21545	1	Superstructure ML 2.35 Saa 155 "VAN"- Universal incl. lifting pad
14050	1	Lifting unit ML 2.35 NxT, Ø140, PD 1550, stroke 1915 mm
12033	1	Ecological hydraulic fluid 10 ltr.
12172	1	M, Mercedes approval and paint type: "S", RAL 7015 grey
11103	1	Document holder AUTOPSTENHOJ
11104	1	Magnetic tool tray set, 1 set = 2 pcs.
		<b>Not part of the approval (options)</b>
11063	1	Set of cables 10 m
14096	1	Cassette ML PD 1550

The **internal arm locking system** installed as standard reliably protects against external influences.

Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Masterlift 2.35 NxT Saav VAN is perfectly completed by a **control system that is both visually and technically convincing.**

**Standard colour:**

Base plate: RAL 7016

Arms: RAL 3020 - optionally with KTL coating

## Options

Wide range of extra pads, depending on vehicle type.  
Special colours on request

**Frame:**

Standard: completely hot-dip galvanized

**Sub-casing:**

Standard: painted

Optional: hot-dip galvanized or plastic coated

**Installation variants:**

## On-floor installation

## Ceiling installation

**Versions:**

Synchronisation and safety via synchronisation bar and toothed rack.

Self-supporting installation, without load on the bottom of the sub-casing.

