# Masterlift 2.35 NxT Pv 160-220 xy MB

Electro-hydraulic twin-ram lift, 3.5 t with repair platforms





Item no.	Piece/set	Part of the approval according to order no. 16061:
14107	1	Superstructure ML 2.35 Pv 160-220 xy
16070	1	Hydraulic unit ML 2.35 NxT, Ø140, PD 1350, Stroke 1915 mm incl. side covers for cassette KA 1550
12033	1	Ecological hydraulic fluid 10 ltr.
12462	1	Mercedes approval and painting type "Pv" - RAL 7015 grey
11102	1	Rubber blocks 40 mm, 1 set = 4 pcs.
11103	1	Document holder AUTOPSTENHOJ
11104	1	Magnetic tool tray set, 1 set = 2 pcs
		Not part of the approval (options)
11063	1	Set of cables 10 m
14096	1	Cassette ML PD 1550

The Masterlift 2.35 NxT Pv repair platform is optimally suited for quick and easy vehicle lifting.

The premium version is constructed of very strong and rigid solid steel that offers a high degree of stability. They are zink coated and painted. Looks great and works great! Alternatively, we also offer an economical version made from a welded profile that is hot dip galvanized.

Various lengths of repair platforms, which come with xy-function in the premium version as standard, make the Masterlift 2.35 NxT the perfect helper in your workshop. Optionally, longitudinally adjustable supports can be supplied instead of the xy function.

The handy, non-slip and form-fitting rubber pads ensure that the vehicle is lifted with pinpoint accuracy. The strong 140 mm diameter cylinders are also designed for long-lasting functionality and further round off the high-quality level, which ensures low maintenance requirements.

Even in the event of a power blackout, the lift can still be lowered without any problems thanks to the pneumatic emergency lowering system.

The Masterlift 2.35 NxT Saa is perfectly completed by a control system that is both visually and technically convincing.

## Standart colour:

Pv Premium: zink coated and painted - RAL 9006 Pv Standard: hot-dip galvanized, without painting

### Options:

Longitudinally adjustable supports Rubber blocks in different heights

Standard: completely hot-dip galvanized

# Sub-casing:

Standard: painted

Optional: hot-dip galvanized or plastic-coated

### Versions:

Synchronisation and safety via synchronisation bar and toothed rack

Self-supporting installation, without load on the bottom of the sub-casing

## Installation variants:

On-floor installation Recessed installation (only for Pv Premium) Ceiling installation

