UPLIFTING COMPANY
AUTOP STENHOJ

MagiX 35

Electro-hydraulic scissor lift, 3.5 t capacity





Application

- ☐ Check-in
- ☐ Repair and maintenance

Approvals / recommendations

- ☐ Volkswagen Group

Description:

- ☐ Double master / slave system
- ☐ Control stand with integrated pump unit and alarm signal
- ☐ Electronic synchronization
- ☐ Emergency lowering valve
- ☐ Sturdy scissor construction
- ☐ No mechanical connection between scissor sections
- ☐ Optimum access to vehicle
- ☐ Low minimum height

Standard colours:

- ☐ Platforms & scissor: RAL 7016 – grey
- ☐ Ramps: RAL 3020 – red

Versions:

- ☐ Available with different voltages
- ☐ For surface-mounting or recession
- ☐ S = superstructure on floor
- ☐ I = superstructure in floor
- ☐ G = galvanized upper plates and base frame

Optional extras:

- ☐ LED-lighting set for surface-mounted versions
- ☐ Set of expansion bolts
- ☐ Set rubber blocks, 40, 60, 70, 80 and 100 mm

Special colours available on request!

Scan the QR-Code
for detailed product information.


Further Information on
www.autopstenhoj.com


AUTOPSTENHOJ GmbH
Sandkampstraße 90
D-48432 Rheine
+49 5971 8602-02
info@autopstenhoj.com


AUTOPSTENHOJ GmbH
Barrit Langgade 188-190
DK-7150 Barrit
+45 76 82 13 30
info@autopstenhoj.com


Technical data	
Lifting capacity	3,500 kg
Lifting height	1,775 mm
Working height	S: 1,880 mm I: 1,770 mm + Rubber pads
Lifting / lowering time	44/44 sec.
Pump unit	3 kW
Voltage	3x230 / 400V – 50 Hz

Scissor platforms	
Platform length	S: 1,560 – 2,100 mm I: 1,526 – 2,001 mm
Platform width	630 mm
Distance between platforms	800 mm
Min. height	S: 105 mm I: 0 mm
Depth of recess	S. 0 mm I: 110 mm











Available with galvanized base frame



Self-lubricating bearing

Illustrations are not binding and optional. Under reserve of dimensional, constructional and technical modifications! Validity 07/2019.