

# **Major 7230**

Electro-hydraulic 4-post lift, 7.2 t capacity





#### Application

- □ Direktannahme
- ☐ Repair and maintenance

### Approvals / recommendations

□ Renault

## Description:

#### Post:

- ☐ Integrated eccentric brake system
- ☐ Emergency stop valve
- □ Obstruction system
- Pneumatic parking system in height adjustable ratchets
- ☐ Pump unit with immersed motor and control unit on rear left post
- $\hfill\square$  Pushbutton control unit with alarm signal
- ☐ Hydraulic cylinder under left platform
- ☐ Lifting and lowering by means of cables
- ☐ Emergency lowering valve

#### Platforms:

- ☐ One movable platform as standard
- ☐ Platforms prepared for AUTOPSTENHOJ scissor jack

#### Standard colours:

- □ Platforms & posts: RAL 7016 grey
- Ramps: RAL 3020 red

## Versions:

- ☐ Available with different voltages
- Drive-on ramps and stops for surface-mounting, alternatively drive-over ramps for recessed installation
- $\square$  S = flush platforms
- ☐ G = galvanized platforms

# Optional extras:

- ☐ Set of expansion bolts
- □ Extra control unit
- LED-lighting set
- ☐ Set of two 385 mm ramp extensions
- ☐ Set of two platform extensions (0.5 m)

Special colours available on request!



Scan the QR-Code for detailed product information.

Further Information on www.autopstenhoj.com

#### **AUTOPSTENHOJ GmbH**

Sandkampstraße 90 D-48432 Rheine

**\** +49 5971 8602-02

info@autopstenhoj.com

#### **AUTOPSTENHOJ GmbH**

Barrit Langgade 188-190 DK-7150 Barrit

**\** +45 76 82 13 30

info@autopstenhoj.com

Technical data	
Lifting capacity	7,200 kg
Lifting height	1,670 mm
Working height	1,840 mm
Lifting / lowering time	approx. 40/58 sec.
Pump unit	3 kW
Voltage	3x230/400V - 50 Hz - 25/16 A

Platforms	
Total length	7,280 mm
Usable length of platform	6,000 mm
Wheel base, min max.	variable
Platform width	630 mm
Distance between platforms	725 – 1,210 mm
Min. height	170 mm
Width between posts	3,000 mm
Total width - outer edges base plates	3,432 mm
Total height	2,235 mm









