

# Biglift 2.65 Saaa

Electro-hydraulic twin-ram lift, 6.5 t capacity, superstructure with arms



## Application

- Repairs and maintenance
- Body work

## Approvals / recommendations

- Saaa 145:  
Volkswagen Group
- Saaa 230:  
Renault,  
Volkswagen Group
- Saaa 265:  
Mercedes-Benz,  
Volkswagen Group

## Description:

### Steel cassette:

- Waterproof steel cassette

### Hydraulic unit:

- Hard-chrome plated cylinder
- Flexible synchronization and safety system
- Corrosion-free guiding elements
- Pump unit with immersed motor
- Hydraulic oil
- Pneumatic emergency lowering
- Programmable pushbutton control unit
- Great stability, even with uneven weight distribution; due to the cylinder diameter of 213 mm

### Superstructure:

- Triple telescopic arms
- Wheel bearing of the first extension arm
- Low minimum height

### Saaa 265:

- Mechanical ratchet system integrated in the hydraulic unit
- Air preparation unit for oiled and regulated compressed air ( min . 6 bar / max . 10 bar )

### Standard colours

- Base plates: RAL 7016 - grey
- Arms: RAL 3020 - red

## Versions:

- Saaa 145, Saaa 230, Saaa 265

### Steel cassette:

- Zinc-coated
- Coated
- Self-carrying (Saaa 230)

### Installation:

- Superstructure on floor
- Superstructure in floor with covers
- Ceiling installation

## Optional extras:

- Large program of extra pads

**Zinc coating and special colours on request!**



Click the QR-Code for detailed product information.

Further Information on [www.autopstenhoj.com](http://www.autopstenhoj.com)

**AUTOPSTENHOJ GmbH**

Sandkampstraße 90  
D-48432 Rheine  
☎ +49 5971 8602-02  
✉ [info@autopstenhoj.com](mailto:info@autopstenhoj.com)

**AUTOPSTENHOJ GmbH**

Barrit Langgade 188-190  
DK-7150 Barrit  
☎ +45 76 82 13 30  
✉ [info@autopstenhoj.com](mailto:info@autopstenhoj.com)

Technical data	
Lifting capacity	6,500 kg
Lifting height	1,865 mm
Working height	2,000 - 2,060 mm
Cylinder diameter	2 x 213 mm
Distance between cylinders	Saaa 145: 1,350 mm Saaa 230: 2,150 mm Saaa 265: 2,650 mm
Lifting / lowering time (high pressure)	approx. 45 sec.
Foundation depth	2,625 mm
Pump unit	3 kW
Hydraulic oil	18 l
Voltage	230 / 400 V – 50 Hz – 16 A

Arm superstructure	
Total width	3,350 mm
Lifting pad included in the delivery	11028 (135 – 195 mm)
Min. height	135 – 195 mm
Drive-through width	Saaa 230: 1,930 mm Saaa 265: 2,430 mm
Arm length, min. - max.	770 – 1,640 mm

