Masterlift 2.30 Sav 230

Electro-hydraulic twin-ram lift, 3 t capacity, superstructure with adjustable arms





Application

- ☐ Repairs and maintenance
- ☐ Body work

Approvals / recommendations

- ☐ Opel
- ☐ Volkswagen Group

Description:

Steel cassette:
- ☐ Waterproof steel cassette

Hydraulic unit:
- ☐ Hard-chrome plated cylinder
- ☐ Flexible synchronization and safety system
- ☐ Corrosion-free guiding elements
- ☐ Pump unit with immersed motor
- ☐ Hydraulic oil
- ☐ Pneumatic emergency lowering
- ☐ Programmable pushbutton control unit

Superstructure:
- ☐ Single telescopic arms
- ☐ Simple arm locking system
- ☐ Low minimum height

Standard colours:
- ☐ Base plates: RAL 7016 - grey
- ☐ Arms: RAL 3020 - red

Versions:

Steel cassette:
- ☐ Zinc-coated
- ☐ Coated
- ☐ Self-carrying

Installation:
- ☐ Superstructure on floor

Optional extras:

- ☐ Large program of extra pads

Zinc coating and special colours on request!

Scan the QR-Code
for detailed product information.


Further Information on
www.autopstenhoj.com

autop Maschinenbau GmbH
Sandkampstraße 90
48432 Rheine | Germany
+49 5971 8602-02
+49 5971 8602-25
info@autopstenhoj.com

STENHØJ A/S
Barrit Langgade 188-190
DK-7150 Barrit
+45 76 82 13 30
+45 76 82 13 31
info@autopstenhoj.com


Technical data	
Lifting capacity	3,000 kg
Lifting height	1,950 mm
Working height	2,075 - 2,125 mm
Cylinder diameter	2 x 123 mm
Distance between cylinders	2,285 mm
Lifting / lowering time (high pressure)	approx. 30 sec
Foundation depth	2,625 mm
Pump unit	3 kW
Hydraulic oil	10 l
Voltage	230 / 400 V – 50 Hz – 16 A

Arm superstructure	
Total width	2,690 mm
Lifting pad included in the delivery	11033 (125 – 175 mm)
Min. height	125 – 175 mm
Drive-through width	2,120 mm
Arm length, min. - max. min. – max.	550 – 845 mm





Pump unit with immersed motor



Hard-chrome plated cylinder



Water-proof cassette
(with certificate)

Illustrations are not binding and optional. Under reserve of dimensional, constructional and technical modifications! Validity 07/2017.