

Mono Flex H 30

High pressure and semi-hydraulic lift, 3 t capacity



Application

- ☐ Wash
- ☐ Repairs and maintenance
- ☐ Body work

Description:

- ☐ Hard-chrome plated cylinder
- ☐ 4 different arm lengths
- ☐ Single telescopic arms
- ☐ 3 different base plates
- ☐ Semi-hydraulic with manouvering valve
- ☐ High pressure for either single or central operation (up to 6 lifts)
- ☐ Automatic arm locking system
- ☐ Available with anti-rotation device
- ☐ Available with pilot valve

Standard colours:

- ☐ Base plate: RAL 7016 - grey
- ☐ Arms: RAL 3020 - red

Versions:

- ☐ Mono Flex H 30 S (645/1,040 mm)
- ☐ Mono Flex H 30 CF (720/1,070 mm)
- ☐ Mono Flex H 30 CF VAN (720/1,070 mm)
- ☐ Mono Flex H 30 CF VAN L (830/1,395 mm)
- ☐ Special version: Mono Flex H 20 CF CAMP (910/1,400 mm) 2,000 kg capacity for lifting caravans
- ☐ S = screw pad
- ☐ CF = combiflex pad

Optional extras:

- ☐ Safety leg
- ☐ Installation frame
- ☐ Extra pads for CF-models
- ☐ Protection bag

Special colours available on request!



Scan the QR-Code
for detailed product information.

Further Information on
www.autopstenhoj.com

autop Maschinenbau GmbH

Sandkampstraße 90
48432 Rheine | Germany

☎ +49 5971 8602-02

☎ +49 5971 8602-25

✉ info@autopstenhoj.com

STENHØJ A/S

Barrit Langgade 188-190
DK-7150 Barrit

☎ +45 76 82 13 30

☎ +45 76 82 13 31

✉ info@autopstenhoj.com

Technical data

Lifting capacity	3,000 kg
Lifting height	1,750 mm
Cylinder diameter	238 mm
Lifting / lowering time (high pressure)	approx. 35 sec
Foundation depth	2,600 mm
Pump unit	3 kW
Hydraulic oil	High pressure: 8 / 40 l Semi-hydraulic: 140 l
Necessary constant air pressure	10 bar
Voltage	230 / 400 V – 50 Hz – 16 A

Arm superstructure

Min. height	100 mm
Arm length, min. - max. min. / max.	645 / 1,040 mm 720 / 1,070 mm 835 / 1,395 mm 910 / 1,400 mm

