

Mono Quick 30

High pressure and semi-hydraulic lift, 3 t capacity



Application

- ☐ Repairs and maintenance

Description:

- ☐ Hard-chrome plated cylinder
- ☐ Adjustable H-shaped superstructure
- ☐ Skidproof rubber pads
- ☐ Semi-hydraulic with manouvering valve
- ☐ High pressure for either single or central operation (up to 6 lifts)
- ☐ Available with anti-rotation device
- ☐ Available with pilot valve

Standard colours:

- ☐ RAL 7016 - grey

Versions:

- ☐ Superstructure 1,400-2,000 mm adjustability lengthwise

Optional extras:

- ☐ Safety leg
- ☐ Installation frame
- ☐ XY-pads
- ☐ Rubber pads

Special colours available on request!



Scan the QR-Code
for detailed product information.

Further Information on
www.autopstenhoj.com

autop Maschinenbau GmbH

Sandkampstraße 90
48432 Rheine | Germany

☎ +49 5971 8602-02

☎ +49 5971 8602-25

✉ info@autopstenhoj.com

STENHØJ A/S

Barrit Langgade 188-190
DK-7150 Barrit

☎ +45 76 82 13 30

☎ +45 76 82 13 31

✉ info@autopstenhoj.com

Technical data

Lifting capacity	3,000 kg
Lifting height	1,750 mm
Cylinder diameter	238 mm
Lifting / lowering time (high pressure)	approx. 35 sec
Foundation depth	2,600 mm
Pump unit	3 kW
Hydraulic oil	High pressure: 8 / 40 l Semi-hydraulic: 140 l
Voltage	230 / 400 V – 50 Hz – 16 A
Necessary constant air pressure	10 bar

Pv superstructure

Min. height	88 mm
Total width	1,650 mm
Total length	2,000 mm

