

Major 5529-55 WL

Electro-hydraulic 4-post lift, 5.5 t capacity



Application

- ☐ Check-in
- ☐ Repair and maintenance
- ☐ Wheel alignment
- ☐ Testing

Description:

Posts:

- ☐ Integrated eccentric brake system
- ☐ Emergency stop valve
- ☐ Obstruction system
- ☐ Pneumatic parking system in height adjustable ratchets
- ☐ Pump unit with immersed motor and control unit on rear left post
- ☐ Pushbutton control unit with alarm signal
- ☐ Hydraulic cylinder under left platform
- ☐ Lifting and lowering by means of cables
- ☐ Emergency lowering valve

Platforms:

- ☐ One moveable platforms as standard
- ☐ Platforms with tolerances of only max ± 1.0 mm length- and crosswise and ± 0.5 mm from left to right
- ☐ Distance pieces covering the entire length, fixated by steel edges in sides
- ☐ Platforms prepared for AUTOPSTENHOJ scissor jack with innovative air supply
- ☐ Platforms on stable cross beams

Standard colours:

- ☐ Spray-galvanized functional surfaces; platforms and posts: RAL 7016 – grey
- ☐ Ramps: RAL 3020 – red

Versions:

- ☐ Available with different voltages
- ☐ Drive-on ramps and stops for surface-mounting, alternatively drive-over ramps for recessed installation
- ☐ WL = with front and rear recesses for turn tables. Side slip plates available as optional extra.
- ☐ 55 = 5,500 mm platforms

Optional extras:

- ☐ Set of expansion bolts
- ☐ Extra control unit
- ☐ LED-lighting set
- ☐ Zinc coating of platforms

Special colours available on request!



Further Information on
www.autopstenhoj.com

✉ info@autopstenhoj.com

✉ info@autopstenhoj.com

Technical data	
Lifting capacity	5,500 kg
Stroke length	1,690 mm
Working height	1,920 mm
Lifting / lowering time	40 / 58 sec.
Pump unit	3 kW
Voltage	3x230/400V – 50 Hz – 16 A inert

Platforms	
Total length	7,455 mm
Usable length of platform	5,500 mm
Wheel base, min. - max.	variable
Platform width	650 mm
Distance between platforms	900 mm
Drive-on height	230 mm
Width between posts	2,900 mm
Total width - outer edges base plates	3,332 mm
Total height	2,235 mm

